

TEAC®

NEW

Product Information



MP3

OGG

Slot Loading



18mm Height Slot Loading DVD Player Drive DV-LC140

- Stable operation in wider range of extreme temperatures
- Shock & Vibration-proof design
- Light Weight Mechanism

Video Output	CVBS (75ohm)
Audio Output (Line Out)	Analog 2ch
Supported Video Output Format	NTSC / PAL
Supported Video Format	DVD Video / Video CD
Supported Audio Format	CD / MP3 / OGG
Supported Disc Media	DVD Video / DVD-R / DVD-RW / DVD+R / DVD+RW CD / CD-R / CD-RW
Supported Disc Size	12cm / 8cm
Supported Memory Card	USB / SD (MMC)
Interface	
Drive Control I/F	IR (Wire connection) , R5232C
I/O Interface	FFC / FPC connector of 0.5mm pitch Power Supply / IR / Video Output / Audio Output / USB / SD
Power Source	+5V (±5%) DC
Reple Pulse Noise	100mVpp or less
Current Consumption	
Playback for DVD Video	1.2A or less
Environmental Conditions	
Temperature Operating	-20 to 70 deg
Operation Performance guarantee	-10 to 65 deg
Temperature Non-Operating	-40 to 85 deg
Humidity Operating	45 to 70 %RH
Humidity Non-Operating	5 to 90 %RH
Vibration Operating (Z-axis)	1.2G (8 to 20Hz) / 2.0G (20 to 200Hz)
Vibration Non-Operating	2.5G (10 to 200Hz) 900sec / Cycle
Shock Non-Operating	80G 11msec (1Surface for 1 Mechanism)
Installation	
Mounting Orientation	Horizontal Front / Back : -10 to +30 / Side to Side : -10 to +10°
Outer Dimension	141.5W x 17.8H x 128.0D (mm)
Mass (Weight)	(250g)
Reliability	
Load / Eject Life	10000 times
MTBF (sequential read / 25deg)	65000POH
Safety / Environment Standards	UL / RoHS



is a trademark of Koninklijke Philips Electronics N.V.



is a trademark of DVD Format/Logo Licensing Corporation registered in the U.S., Japan and other countries.

Corporate and product names are the respective trademarks or registered trademarks of the companies mentioned. Features and specifications are subject to change without notice. Precaution : To ensure safe handling and operation, read the Instruction Manual before use.

TEAC CORPORATION Data Storage Products Division

TEAC CORPORATION (<http://www.teac.co.jp>) 3-7-3 Naka-cho, Musashino, Tokyo 180-8550 Japan Phone:81-42-252-5041 Fax:81-42-255-2554

TEAC AMERICA, INC. (<http://www.teac.com>) 7733 Telegraph Road, Montebello, California 90640, U.S.A. Phone:1-323-726-0303 Fax:1-323-727-7656

TEAC EUROPE GmbH. (<http://www.teac.de>) Bahnstrasse 12, 65205 Wiesbaden-Erbenheim, Germany Phone:49-611-71580 Fax:49-611-7158-392

TEAC SSE LTD. Unit 19&20, The Courtyards Hatters Lane Watford Hertfordshire WD18 8TE, U.K. Phone:44-8451-302515 Fax:44-1923-236290

TAIWAN TEAC CORPORATION (Taipei Office) (<http://www.teac.com.tw>) 3F No.45, Sec.1 Min Chuan E. Road, 104 Taipei Taiwan R.O.C. Phone:886-2-2597-8608 Fax:886-2-2597-8591

TEAC ELECTRONICS (M) SDN BHD (<http://www.teac.com.my>) Lot 22, Batu Berendam Ftz III, Batu Berendam, 75350 Melaka, Malaysia. Phone:60-6-2843402 Fax:60-6-2843471

TEAC SHANGHAI LTD. (<http://www.teacchina.com.cn>) Rm2505-2506, Tower A, City Center of Shanghai 100 Zun Yi road, China 200051 Phone:86-21-6237-2838 Fax:86-21-6237-2732

©Copyright TEAC CORPORATION 2007

PRINTED IN JAPAN 0807 PDF . DS-216